



HYDINT & SUZHIK CONTROLS

ISO 9001:2008 Factory's Owned Marketing Unit for Compressed Air Filtration, Pneumatics, Manual Valves & Pneumatics / Electrical Actuators - INDIA'S #1 BRAND FOR REMOVING MOISTURE FROM THE COMPRESSED AIR

[Home](#) [Products \(HYDINT\)](#) [Pneumatic Products](#) [Manual Valves](#)

info@hydint.com +91 971 298 7360  [Log In](#)



"HYDINT" MOISTURE SEPARATOR, (FEMALE SCREWED (BSP). MODEL: "SILVER+ADB"

(1) MODEL: "SILVER+ADB" - (1/2", SCREWED, WITH MECHANICALLY OPERATED AUTO DRAIN FACILITY)

SPECIFICATIONS / DATASHEET / CATALOGUE OF MODEL: "SILVER+ADB"

BODY	: Aluminium Pressure Die Cast
SIZE	: 15mm (1/2")
FLOW RATE OF SCFM	: 40
FILTER ELEMENT	: SS Coalescer
EFFICIENCY	: 99.99%
DESIGN PRESSURE	: 10kg/sq.cm.
TESTING PRESSURE	: 12kg/sq.cm.
SERVICE LIFE	: 3-5 Years
MAINTENANCE	: No maintenance required in Moisture Separator
SPARES	: No spares required
WARRANTY	: 1 Year (as per our warranty certificate)
MEDIA	: Air
INSTALLATION PREFERRED	: At the end before FRL in each equipment/instrument/tool in vertical position
MINIMUM DISTANCE REQUIRED	: 6 Mtrs. after compressor/air receiver tank
DRAINAGE PROVISION	: Mechanically Operated Auto Drain Facility given
END CONNECTION	: Female Screwed (BSP)
MODEL	: "SILVER+ADB" - (1/2" , Screwed, Mechanically Operated Auto Drain)

(Due to our R&D and the worldwide advancement in technology, we reserve our right to make changes from time to time in technical specifications, datasheet, catalogue, dimension and images without any prior notice)

[Download](#)