



HYDINT & SUZHIK CONTROLS

ISO 9001:2008 Factory's Owned Marketing Unit for Compressed Air Filtration, Pneumatics, Manual Valves & Pneumactical / Electrical Actuators - INDIA'S #1 BRAND FOR REMOVING MOISTURE FROM THE COMPRESSED AIR

[Home](#) [Products \(HYDINT\)](#) [Pneumatic Products](#) [Manual Valves](#)

info@hydint.com +91 971 298 7360

[Log In](#)



"HYDINT" PRE FILTER, (FEMALE SCREWED (BSP),
10KG,

MODEL : "HF-S"

- (1) Model: "HF-S-06" (1/4", Screwed)
- (2) Model: "HF-S-10" (3/8", Screwed)
- (3) Model: "HF-S-15" (1/2", Screwed)
- (4) Model: "HF-S-20" (3/4", Screwed)
- (5) Model: "HF-S-25" (1", Screwed)
- (6) Model: "HF-S-40" (1.1/2", Screwed)
- (7) Model: "HF-S-50" (2", Screwed)

SPECIFICATIONS / DATASHEET / CATALOGUE OF MODEL: "HF-S"

BODY	: Aluminium Pressure Die Cast
BOWL	: P.C. Bowl / Metal Bowl
SIZE	: 8mm (1/4") to 50mm (2")
FILTER ELEMENT	: 5micron
SPARE FILTER ELEMENT	: Available
DESIGN PRESSURE	: 10kg/sq.cm.
TEMPERATURE RESISTANCE	: 50degree C
WARRANTY	: 1 Year (as per our warranty certificate)
APPLICATION	: Removing dust, rust and solid particles
MEDIA	: Air
INSTALLATION PREFERRED	: At the entry level in each equipment/instrument/tool after moisture separator in vertical position
MINIMUM DISTANCE REQUIRED	: 6 Mtrs. after compressor/air receiver tank
END CONNECTION	: Female Screwed (BSP)
MODEL	: "HF-S-06" - (1/4", Screwed) "HF-S-10" - (3/8", Screwed) "HF-S-15" - (1/2", Screwed) "HF-S-20" - (3/4", Screwed) "HF-S-25" - (1", Screwed) "HF-S-40" - (1.1/2", Screwed) "HF-S-50" - (2", Screwed)

(Due to our R&D and the worldwide advancement in technology, we reserve our right to make changes from time to time in technical specifications, datasheet, catalogue, dimension and images without any notification)

[Download](#)