



## HYDINT & SUZHIK CONTROLS

ISO 9001:2008 Factory's Owned Marketing Unit for Compressed Air Filtration, Pneumatics, Manual Valves & Pneumatical / Electrical Actuators - INDIA'S #1 BRAND FOR REMOVING MOISTURE FROM THE COMPRESSED AIR

[Home](#) [Products \(HYDINT\)](#) [Pneumatic Products](#) [Manual Valves](#)

[info@hydint.com](mailto:info@hydint.com) +91 971 298 7360

 [Log In](#)

### "HYDINT" MOISTURE SEPARATORS, FEMALE SCREWED (BSP) MODEL : "COMBO"



- (1) MODEL: "COMBO-01" (1/4", SCREWED, MANUAL DRAIN FACILITY)
- (2) MODEL: "COMBO-01-AT" (1/4", SCREWED, AUTO DRAIN FACILITY)
- (3) MODEL: "COMBO-02" (1/2", SCREWED, MANUAL DRAIN FACILITY)

## SPECIFICATIONS / DATASHEET / CATALOGUE OF MODEL: "COMBO"

BODY	: Aluminium Pressure Die Cast
SIZE	: 8mm (1/4") & 15mm (1/2")
FLOW RATE OF SCFM	: 28 & 40
FILTER ELEMENT	: SS Coalescer
EFFICIENCY	: 99.99%
DESIGN PRESSURE	: 10kg/sq.cm.
TESTING PRESSURE	: 12kg/sq.cm.
SERVICE LIFE	: 3-5 Years
MAINTENANCE	: No maintenance required
SPARES	: No spares required
WARRANTY	: 1 Year (as per our warranty certificate)
MEDIA	: Air
INSTALLATION PREFERRED	: At the end before FRL in each equipment/instrument/tool in vertical position
MINIMUM DISTANCE REQUIRED	: 6 Mtrs. after compressor/air receiver tank
DRAINAGE PROVISION	: Manual / Automatic
END CONNECTION	: Female Screwed (BSP)
MODEL	: "COMBO-01" - (1/4", Screwed, Manual Drain Facility) "COMBO-01-AT" - (1/4", Screwed, Auto Drain Facility) "COMBO-02" - (1/2", Screwed, Manual Drain Facility)

(Due to our R&D and the worldwide advancement in technology, we reserve our right to make changes from time to time in technical specifications, datasheet, catalogue, dimension and images without any notification)

[Download](#)